



STRAPPING HAND TOOL
MODEL: CMT 260



Cyklop CMT 260 - The all-rounder for universal application

The CMT 260 is a well balanced tool with low 3.8 kg weight and variable tension speed. It is usable for most common PP + PET straps (12 – 16 mm). Furthermore this battery handtool convinces by its unrestricted mobility, one hand operation and the simple insertion of the strap.

Strap alignment indicator

Less operating errors

- Avoidance of malfunctions during tensioning/welding/cutting processes
- Avoidance of low seal efficiency

Full Touch Display

Easy to use

- Favorite mode, display lock
- Welding time settings
- Tension force settings
- Operation mode settings

Real time indication of tension force

Higher process reliability and less operating errors

- Indication of selected tension (filled out bars)
- Shows the true tension force during tensioning process

3-colour info display & acoustic signal

Avoidance of malfunction

- Full Touch Display and tool information for operators
- Finished strapping process directly visible and audible

Variable tension speed

Simplified operation and higher reliability

- Slow start-up for arrangements on packaged goods (fixing up edge protectors)
- Inching operation (Cautious approach to correct tension force for the product)

Favorite strapping function

Simplified and quicker operation

- For various packaged goods, with different setting requirements (heavy/light)
- For the use of different PP / PET straps



Technical data

- Strap: PP (Polypropylen) + PET (Polyester)
- Strap width: 12 – 16 mm
- Strap thickness: 0.50 - 1.00 mm
- Weight: 3.8 kg
- Dimension mm: L370 x B141 x H135
- Tension force: 400 – 2500 N
- Tension speed: 0 - 220 mm/s

Cycles per Charge

- Low tension: 800
- Medium tension: 400
- High tension: 200
- Battery: Bosch Li-Ion 18V / 2.0 Ah
- Charger: Bosch

Advantages:

- Stability / robustness
- Full Touch Display
- Variable tension speed
- Favorite strapping function
- Real-time display
- Strap alignment indicator
- Resistant to fall, dust and moisture
- True tension force during process
- Gentle release
- More strapping cycles per battery charge
- Low weight & well balance
- Ergonomic handle
- Reliability of the weld
- Less maintenance

18V Battery and Charger:

- More cycles per charge
- Bosch Li-Ion battery
- Active battery temperature monitoring
- Charging time 15 - 30 min
- Charge status display in %
- Longer lifetime
- Cool Pack technology

Options / Accessories:

- Protection Cover for usage in rough environment
- Protection Plate for abrasive surfaces
- Suspension Bow for static locations

WWW.CYKLOP.COM

DIRECT LINE: +49 (0) 2236 602 0

CYKLOP GmbH
Industriestraße 133
50996 Cologne
Germany
info@cyklop.de

CYKLOP
INTERNATIONAL
THE STRAPPING COMPANY