

STRAP	PAWERED BY	STAP SIZE
PLASTIC	BATTERY	9-32 mm

BATTERY-POWERED TOOLS FOR PLASTIC STRAPPING

Viper



	GT Smart+ C165990812Z	GT One + C155880812Z	Viper C155660812Z	GT Xtreme C160990812Z	GT Max C164990812Z
User-friendly graphical interface	✓	✓	✓	✓	✓
Full TFT color display	-	-	✓	-	-
Capacitive touchscreen	-	-	✓	-	-
Real-time force/speed indication	-	-	✓	-	-
Variable force/speed levels	✓	✓	✓	✓	✓
Values in Newtons, Kg, and lbs	-	-	✓	-	-
Soft mode available	✓	✓	✓	✓	✓
Brushless motors	✓	✓	✓	✓	✓
Cooling time can be set	-	-	✓	-	-
Stores up to 8 settings for later use	-	-	✓	-	-
Tool status information	-	-	✓	-	-
Lockable display	✓	✓	✓	✓	✓
IoT enabled	-	-	✓	-	-
Perfectly ergonomic and lightweight	✓	✓	✓	✓	✓
Registered Italian design	-	-	✓	-	-
Indication cycle finished	✓	✓	✓	✓	✓
Auto-Power-Off	✓	✓	✓	✓	✓
Smoothly opening lever	✓	✓	✓	✓	✓
Indication of number of cycles	✓	✓	✓	✓	✓





	GT Smart+ C165990812Z	GT One + C155880812Z	Viper C155660812Z	GT Xtreme C160990812Z	GT Max C164990812Z
Mode	Manual				
Tensioning Force • Standard • Soft	Automatic / Manual/ Semi-Automatic				
	650/1.800N 240/1.000N	1.200/2.700N 500/1.500N	1.200/2.700N 500/1.500N	2.200/4.200N 1.100/3.100N	2.500/6.500N 1.800/5.000N
Max. tensioning speed	230 mm/sec	200 mm /sec	200 mm /sec	150 mm/sec	80 mm/sec
Sealing efficiency*	75 – 85 %				
Weight (incl.battery)	3,7 Kg	3,75 Kg	3,9 Kg	4,0 Kg	6,2 Kg
Weight (excl. battery)	3,3 Kg	3,3 Kg	3,45 Kg	3,52 Kg	5,45 Kg
Dimension (L x W x H)	330x105x160 mm	330x105x160 mm	369x165x123 mm	330x 105x160 mm	425x135x180 mm
Operating temperature	-5°C to 40°C				
Relative humidity	20 – 90 %				
Noise level	≈96 dB(A)	≈96 dB(A)	≈96 dB(A)	≈96 dB(A)	≈113 dB(A)
Vibration level	<4,94 m/sec ²	<4,94 m/sec ²	<5,1 m/sec ²	<5,85 m/sec ²	<2,5 m/sec ²
PP / PET Strap					
Width	9 – 12– 16 mm	9 – 12– 16 mm	9 – 12– 16 mm	16 – 19 mm	25 – 32 mm
Thickness	0,4-0,85 mm	0,5-1,1 mm	0,5-1,1 mm	0,8 – 1,27 mm	0,9 – 1,3 mm
Battery					
Battery	Akku Power Li-Ion 14,4 V, 3,0 Ah	Akku Power Li-Ion 14,4 V, 4,0 Ah	Makita Li-Ion 18 V, 3,0 Ah - 5,0 Ah (optional)	Akku Power Li-Ion 18 V, 5,0 Ah	Akku Power Li-Ion 36 V, 3,0 Ah
Charger voltage	230 V				
Charging time	≈ 40 min	≈ 50 min	≈ 20 min	≈ 75 min	≈ 75 min
Cycles per charge**	150-200	150-350	150-350/400-550 (with 5 Ah)	180-300	150-300
Video					n.a

OPTIONALS

Additional battery & charger***

Storage case (for tool, 1-2 battery + charger)

Suspension hook [A]

Metal plate that protects strapping foot [B] and bottom shell [C]****

Direct connection system to the power supply line (for usage without battery) [D]*****

*This measure describes in percentages the ability of the strap to maintain its characteristics once sealed, the higher the value the better the seal will be

**Approximate value with maximum voltage and medium package size

***Check the manual and/or contact the appropriate salesperson for option part numbers

****[C] Available for GT Smart+, GT One+ and GT Xtreme

*****[D] Available for GT Smart+ and GT One+

